

Mellau - Mellon

Tekniske data

Konstruktion	Vævet	
Bagside	Latex	
lummateriale	100 % PP	
Total højde	ca. 5 mm	
Total vægt	ca. 2400 g/m ²	
Bredde	70 - 90 - 120 - 200 cm	
Brugsegnet	Erhverv / kontor / bolig	
Trappe	Egnet til trapper	
Antistatiske egenskaber	Permanent antistatisk	
brandtest	T-a	DIN 66081
Øko Tex standard 100		Nr. 23 372
Personopladning	0,09 kV	ÖNORM S 1419/4
Varmetransmissions- modstand	0,059 m ² KW	DIN 52612



Til projekter hvor der kræves B1 brandtest kan produktet Meltrend i 100% polyamid leveres.

Lagervare i 5 farver, special farver fra 200 m².

Fås i bredderne 90-120-200 cm

Mellau - Mellon

Technical details

Manufacturing proces	Woven	
Backing	Latex	
Pile fiber composition	100% PP	
Total height	app. 5 mm	
Total weight	app. 2400 g/m ²	
Width	70 - 90 - 120 - 200 cm	
Application suitability	work areas / offices / domestic	
Stairs	Suitable for stairs	
Static control	Permanent antistatic	
flammability test	T-a	DIN 66081
Øko Tex standard 100		No. 23 372
Impact sound reduction	0,09 kV	ÖNORM S 1419/4
Thermal conductivity	0,059 m ² KW	DIN 52612



For projects where flammability test B1 is required, quality Meltrend in 100% polyamide is recommended.

5 colours available as stockcolours, custommade colours from 200 m².

Available in width 90-120-200 cm