

Technical data

Fraster felt 3 og 5 mm for decoration

Produkt	Felt from fulling. Carded wool in layers, which are felted with moisture, heat, pressure and movement
Material	100% wool felt 5 mm thickness +/- 0,5 mm - 1400 gr/m ² 3 mm thickness +/- 0,3 mm - 820 gr/m ² 0,28 g/cm ³ Merino uld 100% biodegradable Contains no formaldehyde 100% VOC free No chemical irritants free of harmful substances Öeko-tex standard 100 Certified Product Class II Firetest: B1fl - S1 - EN 13501-1 Lightfastness 4-6, ISO skala 1-8
Width	178 cm
Dimensional stability	+/- 1,5%
Backing	Optional: +Stick&Peel Double sided tape consists of a tissue carrier coated on both sides with a modified acrylic dispersion adhesive. It has excellent adhesion properties. it has very good resistance to ageing, climate and temperatur.
Mounting +Stick&Peel	All substrates should be clean and contamination free, a solvent such as isopropyl-alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
Mounting with wet glue	<ol style="list-style-type: none">1. The felt should be adapted to fit the wall/surface before gluing it on. The best result is achieved by carefully measuring the wall and cutting the felt on the cutting table with a digital knife. Any necessary subsequent adjustment of the felt shall be made by cutting the felt with a sharp knife and a ruler in one unbroken cut on a flat surface. It is not recommended to cut the felt after it has been fixed to the wall.2. Glue is applied to the wall in one even layer with a roller, a spatula and/or a brush. Be aware of how long the glue keeps its adhesive properties after it has been applied. If the glue dries up before the felt is put on, its adhesiveness deteriorates. A water based floor adhesive such as Uzin 2000S or Danattack vinyl 246 from Danalim may be used.3. The felt is placed on the wet glue on the wall. Please keep in mind that the felt can be manipulated during application, so that it can be either "shrunk" or stretched. If the felt a little too large for the wall, during application to the wall, one may prefer to "shrink" it instead of having to cut off a piece. "Shrinking" in this context means to contract/ push together the felt by a few percent.4. Immediately after application, the wall is rolled over with a "rolling pin" so that the felt sticks evenly over the whole surface. <p>The above advice is obtained on the basis of practical experience. Fraster can not be held responsible for any consequences caused by following these tips. If in any doubt, we recommend you to have the work done by a qualified professional.</p>
Min. quantity and colors	Felt +Stick&Peel >1m ² , 35 colors from Fraster standard range Cut length >9 m ² , 3 mm felt, 85 colors Cut length >9 m ² , 5 mm felt, 76 colors
Cleaning	Vacuum cleaning. Spot clean with a dry cleaning agent or a damp cloth. For an all over cleaning of the rug, we recommend that you contact a cleaning company that works with the carbonation method in order to avoid the use of soap and chemicals.
More information	www.uk.fraster.dk post@fraster.dk tel. +45 87 88 22 44

