

Technical data
Fraster TwisterPlus



Product	Fraster TwisterPlus
Pile material	100% wool felt 5 mm thick Merino wool 1400 gr/m ² 100% biodegradable Contains no formaldehyde 100% VOC free No chemical irritants free of harmful substances Öeko-tex standard 100 Certified Product Class II Lightfastness 4-6, ISO skala 1-8
Acoustic plate	Nitona acoustic plate, 100% polyester 10 mm Thick. 2800 gr/m ² +/- 10%
Sizes	Standard size 88x88 cm and 59x59 cm. Special sizes on request.
Mounting	50 mm magnetic fitting for wall mounting. 30 mm magnetic fitting for wall mounting. Wire fittings for horizontal or vertical mounting. In the case of a multi-module suspension, it is recommended to mount the modules at a min. 10 mm distance.
Cleaning	Vacuum cleaning. Spot clean with a dry cleaning agent or a damp cloth.
Dimensional stability	+/- 1,5%
Soundabsorption	Norm EN ISO 354:2003 $\alpha_w=0,70$ (H) Absorptions klasse C, when mounting with a 50 mm airgap between wall and TwisterPlus.
Colors	35 colors
Design	25 standard design or bespoke designs
More information	www.fraster.dk post@fraster.dk tlf. +45 87 88 22 44

