

Makalu

Makalu 3510



Makalu 3520




Makalu 3530




Makalu 3540



Makalu 3570



Makalu 3560



Makalu 3550



Fremstillingsmåde	Håndvævet opskåret	Manufacturing process	Handwoven velvet
Luvmateriale	100% polyester	Pile material	100% polyester
Bagside	Bomuld	Backing	Cotton cloth
luvvægt / m ²	ca. 3800 gr/m ² , +/-7,5 %	Pileweight / m ²	app. 3800 gr/m ² , +/-7,5 %
Totalvægt / m ²	ca. 5000 gr/m ² , +/-7,5 %	Total weight / m ²	app. 5000 gr/m ² , +/-7,5 %
Totaltykkelse	ca. 16 mm, +/-7,5 %	Total Height	app. 16 mm, +/-7,5 %
Bredde	500 cm	Width	500 cm
Trinlydsdæmpnings værdi	30db	Impact sound reduction	30db
Gulvarmeegnedhed	SO 8302 0,12 K/W: TOG 1,2	Resistance of heat conduction	ISO 8302 0,12 K/W: TOG 1,2
Brugs klasse EN 1307:2014	Kraftig bolig / normal erhverv	Classification EN 1307:2014	Heavy domestic / General Commercial
Lysægtighed ISO 105 B02:2013	3-4	Colour fastness to light ISO 105 02:2013	3-4
Gnidægtighed tør ISO 105- X12:2016	5	Rubbing fastness- dry ISO 105-X12:2016	5
Gnidægtighed våd ISO 105- X12:2016	5	Rubbing fastness- wet ISO 105-X12:2016	5
Farveægtighed overfor vand ISO 105 E01:2013	5	Colour fastness to water ISO 105 E01:2013	5
Brandklasse BS EN 13501-1:2007	Cfl-S ₁	Burn behaviour BS EN 13501-1:2007	Cfl-S ₁
TOG	1,57	TOG rating	1,57
Trappe egnet	ja	Stairs suitability	yes

