


Yucca

4210 - 4220 - 4230 - 4240 - 4250 - 4260


Fremstillingsmåde	Fladvævet løkkevare
Luvmateriale	100% sisal anti-smudsbehandlet
Bagside	Latex, brandhæmmende behandling (kode 21)
lurvægt / m ²	1350 gr / m ²
Totalvægt / m ²	1930 gr / m ²
Totaltykkelse	5 mm
Bredde	400 + 500 cm
Trinlydsdæmpnings værd	18 db
Gulvvarmeegnethed	ISO 8302 0,1m ² K/W Tog 1
Brandklasse	Bfl-s1

Manufacturing process	Flatwoven looppile
Pile material	100% sisal stain resistant treated
Backing	Latex, fireproof treated (code 21)
Pileweight / m ²	1350 gr / m ²
Total weight / m ²	1930 gr / m ²
Total Height	5 mm
Width	400 + 500 cm
Impact sound reduction	18 db
Resistance of heat conduction	ISO 8302 0,1m ² K/W Tog 1
Fire resistance	Bfl-s1

Yucca 4210



Yucca 4220



Yucca 4230




Yucca 4240



Yucca 4250



Yucca 4260



EN 14041
DOP: 1104-122359
NB: 0493
14
CE





REG.NR
185F14A3
www.pro-dis.info



ENVIRONMENT • CARPETS TESTED FOR A BETTER LIVING